



AMAZE PRO

www.posync.co



POSYNC

PRINTING

Printing method	Thermal dot line printing
Printing method	203dpi, 8dots/mm
Printing speed (Max)	70mm/s
Width	80mm
Valid printing width	72mm
Paper roller diameter	50mm
Paper thickness	60~80μm
Loading	Easy loading mechanism

INTERFACE

Interface	Bluetooth and USB
-----------	-------------------

COMMAND SETS

Command sets	Compatible with ESC/POS
--------------	-------------------------

CHARACTER SET

Font	Font ASCII:9×17,12×24; Multiple code pages support
------	--

BARCODE SYMBOLOGIES

1D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
2D	QR code

GRAPHICS

Graphics	Support bitmap printing with different density and user defined bitmap printing (Max. 40K for per bitmap, and Max. 64K for total)
----------	---

DETECTION

Sensors	Paper out/ low battery
---------	------------------------

CHARGING

Charger	5V/1A adapter
Battery	2000mAh/7.4V rechargeable Li-ion battery. Full charge can print 300~350m (printing density not more than 12.5%) or 250~300mm (printing density not more than 25%)

PHYSICAL CHARACTERISTICS

Working condition	-10°C~70°C , 20%~85%RH
Storage condition	-10°C~70°C, 20%~85%RH
Dimension	110*122.9*67.8mm (W*D*H)
Weight (printer only)	362g (without paper roll and with battery)

SOFTWARE

Emulation	ESC/POS compatible command set
Driver	Windows XP//Win7/Win8/Win10



Tel: 85588 06616 Sales: sales@posync.co Support: support@posync.co