



AMAZE

www.posync.co



POSYNC

PRINTING

| | |
|--------------------------|---|
| Printing Method | Thermal Line |
| Effective Printing Width | 48mm |
| Resolution | 384 dots / line (8 dots/mm, 203 dpi) |
| Printing Speed | 65mm/sec |
| Line Spacing | 3.75mm (can adjust line spacing by command) |
| Font's Font A: | A:32 character / line |
| Font B: | B:42 character / line |
| Character Size | ANK character, Font A:1.5×3.0mm (12×24 dots), Font B:1.1×2.1mm (9×17 dots Simplified) |



BARCODE CHARACTER

| | |
|---------|------------------------|
| Barcode | 1D Barcode, 2D Barcode |
|---------|------------------------|

GRAPHICS PRINTING

| | |
|-------------------|---|
| Graphics Printing | Supports BITMAP download and print (Download up to 5 BITMAPS) |
|-------------------|---|

COMMUNICATIONS

| | |
|-------------------|--|
| Bluetooth and USB | Bluetooth Version 5.0 with EDR, USB Serial Communication |
|-------------------|--|

POWER

| | |
|-------------|--------------|
| Lithium-ion | 2600mAh 7.4V |
| Charger | 10.2V / 1A |



PHYSICAL FEATURES

| | |
|------------|---------------------|
| Weight | 290 gms, Portable |
| Dimensions | 120mm x 70mm x 40mm |

CERTIFICATIONS

| | |
|----------------|-----------------|
| Certifications | STQC, BIS, RoHS |
|----------------|-----------------|

OS SUPPORTED

| | |
|--------------------|-------------------------------|
| Embedded / Generic | Windows, Linux, Android & iOS |
|--------------------|-------------------------------|

SDK

| | |
|--------------------|---|
| STQC Certified RDS | Aadhaar Registered Device Service Supported |
| Protocol | ESC Sequence Protocol |



The information contained herein is subject to change without notice. POSYNC shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies. Intel, Core, is trademarks or registered trademarks of Intel Corporation or its subsidiaries in the U.S. and other countries.

